

Maximale Rollladenhöhe inkl. Kasten

Profil PA39 (mit Führungsschienen PP53 PP45 PK53 PU29 PPD)

Kastengröße	MAXIMALE ROLLADENHÖHE [mm]		
	SW 40	SW 40 + PZ 45	SW 40 + PW 40
SK 125	1240	1280	-
SP/SP-E/SK/SKP 137	1560	1600	-
SP-E/SK/SKP 150	1960	1990	-
SP/SP-E/SK/SKP 165	2390	2470	2030
SP/SP-E/SK/SKP 180	2950	3020	2520
SP/SP-E/SK/SKP 205	4320	4210	3480

Kastengröße	MAXIMALE ROLLADENHÖHE [mm]		
	SW 60	SW 60 + PZ 68	SW 60+ PW 60
SP/SP-E/SK/SKP 137	1440	1210	-
SP-E/SK/SKP 150	1800	1640	-
SP/SP-E/SK/SKP 165	2280	2120	1450
SP/SP-E/SK/SKP 180	2790	2630	1930
SP/SP-E/SK/SKP 205	4050	3780	3400

Kastengröße	MAXIMALE ROLLADENHÖHE [mm]		
	SW 40	SW 40 + PZ 45	SW 40 + PW 40
SKO /SKO-P 137	1560	1600	-
SKO-P 150	2040	2110	-
SKO/SKO-P 165	2430	2510	2080
SKO /SKO-P 180	3260	3100	2910
SKO /SKO-P 205	4370	4250	3950

Kastengröße	MAXIMALE ROLLADENHÖHE [mm]		
	SW 60	SW 60 + PZ 68	SW 60 + PW 60
SKO /SKO-P 137	1410	1250	-
SKO-P 150	1920	1760	-
SKO /SKO-P 165	2320	2160	1450
SKO /SKO-P 180	3060	2640	2330
SKO /SKO-P 205	4130	3820	3410

Kastengröße	MAXIMALE ROLLADENHÖHE [mm]		
	SW 40	SW 40 + PZ 45	SW 40 + PW 40
SKT/170	1890	1690	1220
SKT/210	3230	3310	2860
SKT/240	4460	4770	3940

Profil PA39+Insektenschutz (mit Führungsschienen PPD053)

Kastengröße	MAXIMALE ROLLADENHÖHE [mm]		
	SW 40	SW 40 + PZ 45	SW 40+ PW 40
SK/SKP/SP-E 150	1290	1330	-
SK/SKP/SP/SP-E 165	1730	1690	1380
SK/SKP/SP/SP-E 180	2440	2240	1780
SK/SKP/SP/SP-E 205	2500	2500	2500
SKO-P 150	1250	1330	-
SKO/SKO-P 165	1650	1690	1300
SKO/SKO-P 180	2440	2480	2050
SKO/SKO-P 205	2500	2500	2500